

SCALEOVIEW D22W-1GT

22 Inch LCD widescreen Display

Issue May 2008

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW D22W-1GT widescreen display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design and fashion glare type panel, the SCALEOVIEW D22W-1G fits perfectly into your home environment.

Highlights

- § 22-inch widescreen display with fashion glare type panel
- § Perfect viewing experience at high resolution (incl. 1080i)
- § Stylish black design with a glossy black front
- § DVI-D input supports HDCP
- § Theme mode for optimized picture
- § Frame rate conversation

Ergonomics

- § Optimum flicker-free and distortion-free picture
- § Excellent color purity
- § Well balanced brightness uniformity
- § Excellent Advanced Contrast Ratio(5000:1)
- § Space saving design

Technical highlights

- § 22" (55.9 cm) LCD widescreen display
- § Excellent contrast (ACR) 5000:1
- § Brightness 300 cd/m²
- § Fast response time (typ.) 5 ms
- § DVI interface with HDCP support

Reliability

- § Low power consumption
- § Power management according to EPA
- § Guaranteed quality and stability



Visible screen diagonal	22 inch (55.9 cm)
Resolutions	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
Picture size	473.76 x 296.1 mm
Colors	16.7 million
Pixel Pitch	0.282 mm
Frequencies	
Horizontal	31 - 83 kHz
Vertical	56 - 76 Hz
Brightness (typical)	300 cd/m ²
Advanced Contrast Ratio	5.000:1
Viewing angle (CR<=5)	
Horizontal	170°
Vertical	170°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Menu language (16 languages)	
Power saving mode	
Input signal select	
Theme Mode	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Factory recall setting	
OSD Language	
English, German, Spanish, Portuguese, French, Italian,	
Russian, Swedish, Dutch, Finnish, Danish, Norwegian,	
Polish, Chinese, Japanese	
Base	
Tilt angle	-5° / +15°
Video input	1x D-SUB, 1x DVI-D (HDCP support)
Audio input / output	
Audio signal input	3.5 mm stereo phone jack
Audio output	1.5 W (L) + 1.5 W (R)

Electrical values (internal power supply)

Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw (EPA)	
EPA 'On Mode'	27 W
Max.	< 41 W
Stand by	< 0.8 W
Protection class	1

Temperatures/ dimensions/ weight

Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	424 x 510 x 226 mm
Weight (Monitor only)	4.94 kg

Reliability

MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	

Compliance with standards

Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 2004/108/EEC (EN55022/B, EN55024 EN61000-3-2/-3); RoHS, IT-Eco-declaration, Energy Star (EPA 4.1)
Ecology	

Accessories

Power cable (1.5 m)*	1x wall socket (Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5 mm stereo phone jack
* detachable on display	

Special features

Standardized mounting
interface according
VESA FPMPI (100 mm)
Kensington Lock

Order code	S26361-K1231-V180
EAN	4333643535278